

AW869B

Single band WiFi6 + BT5.2 Module Spec

拟制 Design	审核 Check	批准 Approve	版本 Version	日期 Date
			V1.1	2021.08.24

更改记录:

Reversion History:

版本 Version	日期 Date	更改内容 Modification
1.0	2021.04.27	First release
1.1	2021.08.24	Updata Bluetooth version



目录

Contents

1. Overview.....	3
2. Features.....	3
3. Block Diagram.....	4
4. General Specification.....	4
5. RF Specification.....	5
5.1 Wifi RF Specification.....	5
5.2 Bluetooth Specification.....	7
6. Recommended Operating Rating.....	8
7. Physical Dimensions.....	8
8. Pin Description.....	9
9. Supplier.....	10
10. Physical Photo.....	11
11. Layout Recommendation.....	11
12. Baking & Storage Temperature & Recommended Reflow Profile.....	12
12.1 Baking & Storage Temperature.....	12
12.2 Recommended Reflow Profile.....	13
13. Packing Information.....	13
13.1 Carrier Size Detail.....	13
13.2 Packaging Detail.....	14


1. Overview

The AW869B is a highly integrated module with single band WiFi6,BT5.2;combination solution to support 1 × 1 IEEE 802.11b/g/n/ax WLAN standards and BT 5.2 enabling seamless integration of WLAN/BT and low-energy technology.

2. Features

- Supports a low-power SDIO 2.0 interface for WLAN and a HS-UART/PCM interface for BT
- Provides a highly integrated WLAN system-on-chip (SoC) for 2.4 GHz 802.11ax
- Support WLAN 2.4GHz WiFi6, Supports 20 MHz/40 MHz
- Supports BT 5.2, BLE, and ANT+ and backward compatibility with BT 1.x and BT 2.x + Enhanced Data Rate
- Supports a single-ended RF port for cleaner and lower cost design
- Supports STA,AP,WiFi Direct modes concurrently
- Supports WiFi6 TWT
- Supports MU-MIMO,OFDMA

3. Block Diagram



4. General Specification

Model	AW869B
Product Name	WLAN 802.11b/g/n/ax SDIO2.0 1T1R + Bluetooth 5.2 module
Major Chipset	8800D
Standard	802.11b/g/n/ax
Modulation Method	BPSK/ QPSK/ 16-QAM/ 64-QAM/256-QAM/1024-QAM
Frequency Band	2.4GHz
WiFi Interface	SDIO2.0
BT Interface	UART
Operating Temperature	-20° C ~ 70° C
Storage Temperature	-20° C ~ 125°C
Humidity	5% to 90% maximum
Dimension	12x12x1.6 (LxWxH) ±0.2mm

5. RF Specification

5.1 Wifi RF Specification

Feature	Description
WLAN Standard	IEEE 802.11b/g/n/ax WiFi compliant
Frequency Range	2.400 GHz ~ 2.497 GHz (2.4 GHz ISM Band)
Number of Channels	2.4GHz : Ch1 ~ Ch14
Modulation	802.11b : DQPSK, DBPSK, CCK 802.11 g/n : OFDM /64-QAM, 16-QAM, QPSK, BPSK 802.11 ax : OFDMA /1024-QAM, 256-QAM, 64-QAM, 16-QAM, QPSK, BPSK
Output Power	802.11b / 1Mbps : 17dBm ± 2 dB @ EVM ≤ -10dB 802.11b /11Mbps : 17dBm ± 2 dB @ EVM ≤ -15dB
	802.11g / 6Mbps : 17dBm ± 2 dB @ EVM ≤ -5dB 802.11g /54Mbps : 15 dBm ± 2 dB @ EVM ≤ -28dB
	802.11n /MCS0 : 16 dBm ± 2 dB @ EVM ≤ -5dB 802.11n /MCS7 : 14 dBm ± 2 dB @ EVM ≤ -30dB
	802.11ax /HE0(20/40M) : 16 dBm ± 2 dB @ EVM ≤ -5dB 802.11ax /HE11(20/40M) : 13 dBm ± 2 dB @ EVM ≤ -32dB
Receive Sensitivity (11b,20MHz) @8% PER	- 1Mbps PER @ -93 dBm, typical
	- 2Mbps PER @ -90 dBm, typical
	- 5.5Mbps PER @ -88 dBm, typical
	- 11Mbps PER @ -86 dBm, typical
Receive Sensitivity (11g,20MHz) @10% PER	- 6Mbps PER @ -91 dBm, typical
	- 9Mbps PER @ -89 dBm, typical
	- 12Mbps PER @ -86 dBm, typical
	- 18Mbps PER @ -83 dBm, typical
	- 24Mbps PER @ -80 dBm, typical
	- 36Mbps PER @ -77 dBm, typical
	- 48Mbps PER @ -74 dBm, typical
- 54Mbps PER @ -72 dBm, typical	
Receive Sensitivity (11n,20MHz)	- MCS=0 PER @ -90 dBm, typical
	- MCS=1 PER @ -87 dBm, typical
	- MCS=2 PER @ -84 dBm, typical
	- MCS=3 PER @ -81 dBm, typical
	- MCS=4 PER @ -78 dBm, typical

	- MCS=5 PER @ -75 dBm, typical
	- MCS=6 PER @ -72 dBm, typical
	- MCS=7 PER @ -70 dBm, typical
Receive Sensitivity (11n,40MHz) @10% PER	- MCS=0 PER @ -87 dBm, typical
	- MCS=1 PER @ -84 dBm, typical
	- MCS=2 PER @ -81 dBm, typical
	- MCS=3 PER @ -78 dBm, typical
	- MCS=4 PER @ -75 dBm, typical
	- MCS=5 PER @ -72 dBm, typical
	- MCS=6 PER @ -69 dBm, typical
	- MCS=7 PER @ -67 dBm, typical
Receive Sensitivity (11ax,20MHz) @10% PER	- HE=0 PER @ -90 dBm, typical
	- HE=1 PER @ -88 dBm, typical
	- HE=2 PER @ -86 dBm, typical
	- HE=3 PER @ -84 dBm, typical
	- HE=4 PER @ -81 dBm, typical
	- HE=5 PER @ -79 dBm, typical
	- HE=6 PER @ -76 dBm, typical
	- HE=7 PER @ -73 dBm, typical
	- HE=8 PER @ -70 dBm, typical
- HE=9 PER @ -68 dBm, typical	
Receive Sensitivity (11ax,40MHz) @10% PER	- HE=0 PER @ -88 dBm, typical
	- HE=1 PER @ -86 dBm, typical
	- HE=2 PER @ -83 dBm, typical
	- HE=3 PER @ -80 dBm, typical
	- HE=4 PER @ -77 dBm, typical
	- HE=5 PER @ -74 dBm, typical
	- HE=6 PER @ -72 dBm, typical
	- HE=7 PER @ -69 dBm, typical
	- HE=8 PER @ -66 dBm, typical
- HE=9 PER @ -64 dBm, typical	
Maximum Input Level	802.11b : -10 dBm
	802.11g/n/ax : -20 dBm
Antenna Reference	Small antennas with 0~2 dBi peak gain

5.2 Bluetooth Specification



Feature	Description
General Specification	
Bluetooth Standard	Bluetooth V5.2 of 1, 2 and 3 Mbps.
Host Interface	UART
Antenna Reference	Small antennas with 0~2 dBi peak gain
Frequency Band	2402 MHz ~ 2480 MHz
Number of Channels	BR/EDR :79 channels;BLE:40 channels
Modulation	FHSS, GFSK, DPSK, DQPSK
RF Specification	
Output Power, tolerance±2dBm	
BDR Output Power	7 dBm
EDR Output Power	7 dBm
BLE Output Power	7 dBm
Sensitivity, tolerance±2dBm	
Sensitivity @ BER=0.1% for GFSK(1Mbps)	-96 dBm
Sensitivity @ BER=0.01% for π/4-DQPSK(2Mbps)	-91 dBm
Sensitivity @ BER=0.01% for 8DPSK(3Mbps)	-89 dBm
Sensitivity @ BLE=30.8% for LE(1Mbps)	-100 dBm
Sensitivity @ BLE=30.8% for LE(2Mbps)	-98 dBm
Maximum Input Level	GFSK(1Mbps): -20 dBm
	π/4-DQPSK(2Mbps): -20 dBm
	8DPSK(3Mbps): -20 dBm

6. Recommended Operating Rating


Symbol	Parameter	Minimum	Typical	Maximum	Units
VDD	3.3V supply voltage	3.0	3.3	3.6	V
VDDIO	I/O supply voltage	1.7	1.8	1.9	V
Current	3.3V rating current	--	--	350	mA

7. Physical Dimensions

(Unit: mm)



8. Pin Description




NO.	Name	Type	Description
1	GND	—	Ground connections
2	RF	I/O	WL_BT RF I/O port (2.4G)
3	GND	—	Ground connections
4	BT_ANT	I/O	BT_RF (BT Alone)
5	GND	—	Ground connections
6	Host wake BT	I	Host wake BT(GPIOB5)
7	BT wake host	O	BT wake host (GPIOB3)
8	NC	—	No connect, keep floating
9	VDD	P	3.3V INPUT
10	NC	—	No connect, keep floating
11	NC	—	No connect, keep floating
12	WL_DIS	I	Power key(L=off, H=ON)
13	WL Wake-up host	O	WL Wake-up host (GPIOB2)
14	SD_DAT2	I/O	SDIO DATA2
15	SD_DAT3	I/O	SDIO DATA3
16	SD_CMD	I/O	SDIO command line
17	SD_CLK	I/O	SDIO CLK
18	SD_DAT0	I/O	SDIO DATA0

19	SD_DAT1	I/O	SDIO DATA1
20	GND	—	Ground connections
21	NC	—	No connect, keep floating
22	VDDIO	P	I/O Voltage supply input 1.8V
23	NC	—	No connect, keep floating
24	LPO	—	No connect, keep floating
25	NC	—	No connect, keep floating
26	NC	—	No connect, keep floating
27	NC	—	No connect, keep floating
28	NC	—	No connect, keep floating
29	NC	—	No connect, keep floating
30	NC	—	No connect, keep floating
31	GND	—	Ground connections
32	NC	—	No connect, keep floating
33	GND	—	Ground connections
34	BT_DIS	—	Reserved (GPIOB7)
35	NC	—	No connect, keep floating
36	GND	—	Ground connections
37	UART0_TX	O	No connect, keep floating(Debug PIN)
38	UART0_RX	I	No connect, keep floating(Debug PIN)
39	NC	—	No connect, keep floating
40	NC	—	No connect, keep floating
41	UART_RTS	O	Bluetooth UART interface
42	UART_TX	O	Bluetooth UART interface
43	UART_RX	I	Bluetooth UART interface
44	UART_CTS	I	Bluetooth UART interface

9. Supplier


Supplier list	
Name of material	Material brand
Crystal	JWT/FK/TKD/Murata/TXC
Duplexer	ACX/GLEAD/Sunlord/Walsin
Inductor	Sunlord/ CHILISIN/ SAMWHA/Murata
Wifi chip	Allwinner
Capacitance	SAMSUNG /EYANG
Resistance	UniOhm /YAGEO
PCB(12x12x0.5mm)	A,O,I,F

10. Physical Photo



说明：PCB 不同供应商，底部丝印有微小差异

11. Layout Recommendation



(Top view)

12. Baking & Storage Temperature & Recommended Reflow Profile

(烘烤, 储存温度和推荐炉温)

12.1 Baking & Storage Temperature


- Storage life: 12 months. Storage conditions: 40°C. Relative humidity: $90\% \text{R.H.}$
(保存期限: 12个月, 储存环境条件: 温度在: 40°C, 相对湿度: $90\% \text{R.H.}$)
- After this bag is opened, devices that will be subjected to infrared reflow, vapor-phase reflow, or equivalent processing must be .(模块包装被拆后, SMT 组装之时限)
 - ✓ Check the humidity card :stored at $\leq 20\% \text{RH}$. If :30%~40%(pink) or greater than 40%(red). Labeling module has moisture absorption. (检查湿度卡: 显示值应小于30% (蓝色), 如: 30%~40%(粉红色) 或者大于40% (红色) 表示模块已吸湿气.)
 - ✓ Mounted within 168 hours at factory conditions of: $t \leq 30^{\circ}\text{C}$, $\leq 60\% \text{R.H.}$
(工厂环境温度湿度管制: $\leq 30^{\circ}\text{C}$, $\leq 60\% \text{R.H.}$, 168小时内.)
 - ✓ Once opened, the workshop the preservation of life for 168 hours.
(拆封后, 车间的保存寿命为168小时.)
- Module apart packing after 168 hours, If baking is required, devices may be baked for.
(如在拆封后的168个小时内未使用完, 需要烘烤, 烘烤条件如下:)
 - ✓ Modules must be to remove module moisture problem. (模块须重新烘烤, 以除去模块吸湿问题.)
 - ✓ Baking temperature: $40^{\circ}\text{C} \pm 5^{\circ}\text{C}$, 120 hours. (烘烤温度条件: $40^{\circ}\text{C} \pm 5^{\circ}\text{C}$, 120小时).
 - ✓ After baking, put proper amount of desiccant to seal packages.
(烘烤后, 放入适量的干燥剂再密封包装)

12.2 Recommended Reflow Profile

Referred IPC/JEDEC standard.


Peak Temperature : <math><250^{\circ}\text{C}</math>

Number of Times : 2 times




13. Packing Information

13.1 Carrier Size Detail



ITEM	W	A0	B0	K0	P	F	E	D	P0	P2	T
DIM	24	12.5	12.5	2.8	16	13.25	1.75	1.50	4	2	0.3
TOLE	+0.30 -0.30	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.10 -0.10	+0.05 -0.05

13.2 Packaging Detail



Color of plastic disc: blue
A roll of 1300pcs(前后留空20pcs)

inner box K3K:
33.5cm*34.7cm*7cm
A box of 1300 PCS

carton K=A:
36.4*35.7*37.5cm
A case of 6500 PCS



ESD CAUTION

The AW869B module is ESD (electrostatic discharge) sensitive device and may be damaged with ESD or spike voltage. Although AW869B module is with built-in ESD protection circuitry, please handle with care to avoid the permanent malfunction or the performance degradation.